

## Hood type dishwasher - up to 60 racks, 1080 plates / 2160 glasses / hour



Accessories not included

- **READY TO INSTALL** - incl. drain pump, fill & drain hoses, 3 phase power lead & non-return valve
- **RINSE PRESSURE PUMP** to guarantee rinse pressure and volume
- **Fully enclosed 4 sided hood design** -avoiding loss of energy / steam & minimizing noise
- **EASY-LIFT** hood - 50% less operator effort required to open hood
- **SMARTRONIC** Single button control with colour coded status indication and ergonomically positioned
- Optimum hygienic safety by deep drawn tank with covered corners (no welds) and **SELF-CLEANING CYCLE**
- Chemical dispensers available as optional kits
- Includes 1 plate & flat rack, plus cutlery basket

### Technical Data

1. flexible drain hose 2000mm	20mm inner / 25mm outer diam.
2. fresh water connection: pressure hose 2000mm flow pressure	R 3/4" inside 0.5 - 10 bar 55-65°C
3. power cord	2500mm - no plug
4. hose for detergent 5. hose for rinse aid	Available as optional kits
cycle times <sup>1)</sup>	60 sec. 90 sec. 120 sec.
water consumption	2.5 litres / rack
tank capacity	21 litres
tank heating	2.5kW interlocked
power supply	415/50/3NE
booster loading	6.15kW
total loading	7kW
pump capacity	0.7kW
bench to bench (internal dimension)	628mm
loading height	440mm
noise level	65 dB(A)
weight net	appr.105kg

<sup>1)</sup> To reach the set rinse temperature even with cold water connection, the actual cycles times extend accordingly

Water hardness should not exceed 3°dH, if higher we recommend using a water softener.

If mineral content is high a demineraliser may be advisable.

